



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/14, H04Q 11/04, H04L 29/06	A1	(11) International Publication Number: WO 99/65186
		(43) International Publication Date: 16 December 1999 (16.12.99)

(21) International Application Number: PCT/EP99/03950

(22) International Filing Date: 7 June 1999 (07.06.99)

(30) Priority Data:

1009342	8 June 1998 (08.06.98)	NL
1009987	2 September 1998 (02.09.98)	NL

(71) Applicant (for all designated States except US): KONINKLIJKE KPN N.V. [NL/NL]; Stationsplein 7, NL-9726 AE Groningen (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VAN DER WAL, Jacobus, Cornelis [NL/NL]; Kwekerijstraat 22, NL-2613 VE Delft (NL). VAN LIEROP, Jeroen, Jozef [NL/NL]; Pr. Bernardlaan 47, NL-2274 HV Voorburg (NL). MANDJES, Michael, Robertus, Hendrikus [NL/NL]; Abel Tasmankade 57, NL-2014 AE Haarlem (NL).


(74) Agent: KLEIN, Bart; Koninklijke KPN N.V., P.O. Box 95321, NL-2509 CH The Hague (NL).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: SYSTEM FOR CHARGING THE USE OF A PACKET-BASED TELECOMMUNICATION NETWORK



(57) Abstract

System for charging the use of a packet based telecommunication network. A measuring device (2) measures the number (n) of data units during a period of time (T) or the period of time (t) between a certain number (N) of data units. At any rate, the period of time is short in relation to the total connection time. A calculation device (4) calculates per period of time the number of data units per unit of time and transmits that calculation result (r) to a billing system (5). If the telecommunication system comprises system data units which comprise an indication (r1) of the capacity or priority requested by the user, that indication can also be passed on to the billings system, as well as an indication of the capacity or priority assigned by the telecommunication system.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-1-

System for charging the use of a packet-based telecommunication network.

BACKGROUND OF THE INVENTION

5 The invention is related to a system for charging the use of a packet-based telecommunication network, such as an ATM or IP oriented network.

a. ATM (Asynchronous Transfer Mode)

ATM is a relatively new network technique for supplying
10 connections with very different characteristics in a uniform manner. For each ATM connection has to be paid. Preferably, the amount charged for the connection reflects both the performance delivered by the network and the performance experienced by the customer. In a telephone
15 network something like this is achieved by letting the amount to be dependent on the duration of the connection (calculated in seconds, minutes or other units, such as "ticks") and on the distance covered. A telephone call, however, is almost always a case of a connection with a
20 fixed capacity (e.g. 64 kbit/s with ISDN). In contrast, ATM is much more flexible and there are more connection parameters and variables than with PSTN or ISDN based connections.

- With ATM connections can be established with varying
25 capacity (some kbit/s up to hundreds of Mbit/s).

- With ATM connections can be established with varying network guarantees concerning cell loss, cell delay, cell delay variance and throughput by choosing an "ATM Transfer Capability" (ATC) [2] and Quality of Service class (QoS
30 class) [3]. The amount charged for an ATM connection should preferably also reflect this additional flexibility, which is the subject of the present invention. An important aspect in determining the manner of charging for ATM connections is the direction (incentive) that the charging
35 gives to the manner of network usage. In a traditional telephone network the time-related charge usually assures

-2-

that the customer does not unnecessarily occupy the the connection. In a traditional data network usually a volume rate is used, so that there is an incentive not to burden the network with unnecessary traffic. Another example is
5 the application of an off-peak rate with a view of shifting a part of the network traffic to periods outside the peak hours so that the network can be dimensioned smaller and thereby is less expensive.

The present state of the art usually envisages to base the
10 charge of an ATM connection on two variables, i.e. a time component, the duration of time of the connection (session), and a volume component, the total number of ATM cells transmitted and/or received during the connection [1]. Both variables can easily be measured, registered and
15 processed into a charge during the connection. On processing of the values of the time component the price per unit can depend on various quantities. Examples of such quantities are the distance covered and time of the day or
~~of the week, comparable with the usual charging for~~
20 telephone. Examples of other quantities are the ATM parameters such as the Peak Cell Rate of the connection etc.

There are different ATCs standardised in ITU-T recommendation I.371. Hereafter it is indicated what are
25 the limitations for some of the ATCs of choosing a charge which is based on the time and volume component as described in the above.

A charge which is exclusively based on the time and volume component as set out in the above, has as a consequence
30 that only the total connection duration and only the total number of cells during the duration of the connection play a role in the charge. For these quantities (and thereby for the charge) it does not matter whether all cells are offered evenly over the connection duration ("Constant Bit

Rate") or are concentrated in one or more bursts of cells ("Variable Bit Rate"). For the network it is advantageous if the cells offered are spread as much as possible. ATM connections that use SBR (Statistical Bit Rate) are

5 characterised by two additional parameters, the Sustainable Cell Rate (SCR) and the Maximum Burst Size (MBS). The essence of the situation set out above does not change, however: the user experiences no incentive to spread the cells as much evenly as possible, while this is beneficial

10 for the total network capacity and consequentially is pursued by the network operator. The question is thus in which way the user can be urged to offer the traffic as evenly as possible. In other words, a method is needed to urge the network user via the charging mechanism to offer

15 the traffic in a less bursty way. If in an ATM network use is made of an ABR (Avaialable Bit Rate) control mechanism, the network dynamically assigns capacity to each connection. It can however occur that the network assigns

~~capacity to a connection but that the user does not use or~~

20 not completely use that capacity., e.g. if the user sends less cells than the assigned capacity allows. With the present charging mechanisms (based on a total time and a total volume component in the charge), leaving capacity assigned by the network unused leads to a lower charge.

25 There is no incentive to use the assigned capacity indeed and there is no incentive to gear the capacity to the actual current need.

b. IP (Internet Protocol)

The IP is a connectionless packet switched technique which

30 is used for the Internet. Current IP networks exclusively supply a so-called best-effort service. The networks commits itself to make an effort to deliver the packet (datagramme) at the destination but no guarantee is given; the packet can be lost in case of a congestion. It is

customary to charge access to the Internet only, e.g. by a fixed amount per month (flat rate) or by a fixed rate per unit of time (hour) that the user is logged onto his Internet Service Provider. In this type of charging there is
5 no relation with the amount of data which a user asks or offers.

Because IP is a connectionless technique, there is no matter of "connections" in the same sense as with a telephone or an ATM connection. The aspect of time is
10 therefore inherently unsuitable to serve as measure for network load. To be able to relate the use of an IP network to the network load caused by the network user, another quantity has to be used.

The amount of data can in IP be expressed in different
15 units, such as the number of datagrammes per unit of time and the number of bytes (or bits) per unit of time of which the datagrammes consist.

Guaranteed IP services

~~Recently, work is being done on an extension of the~~
20 services which an IP network can offer. The aim is, next to the best-effort service described in the above, to also enable an IP network to give guarantees for the throughput and for the delay experienced in the network, comparable with the possibilities that an ATM network offers. The
25 standardisation of these new services with guarantees is still in an early stage.

One of the proposed possibilities is to use reservations, e.g. with the protocol RSVP [4]. In that case it is desirable that the extent of the reservation requested or
30 made and the duration of the reservation is expressed in the charge.

In another proposed approach, some bits in the IP header are used to indicate to which service class the IP packet belongs, e.g. "best-effort" or "guaranteed with short

-5-

delay". In that case it is desirable that the indication of the service class also is expressed in the charge.

All considerations as mentioned above for ATM/DBR and ATM/SBR are mutatis mutandis also applicable on these new
5 IP services with guarantees.

SUMMARY OF THE INVENTION

The invention provides a charging system in which the charging gives more direction to an efficient network use. To this end, the invention proposes not to measure and
10 charge the total number of data units (cells, IP datagrammes, bytes in IP datagrammes) during the whole connection (session), but to subdivide a connection in shorter or longer measuring periods, to measure the number of data units during such measurement periods and base the
15 charging on that. The invention comprises hereunto a measurement device for measuring the number of data units received and/or transmitted during a set period of time, shorter than the time during which said telecommunication
~~connection is open or active. In stead of measuring the~~
20 number of data units over a fixed period, it is conversely also possible to measure the duration of time between the reception or transmission of a specific number of data units. Furthermore, the invention comprises a calculation device for calculating for each set or measured period of
25 time the number of data units per unit of time and offering that calculation result a billing system. The calculation device calculates thus per \hat{u} shorter or longer \hat{u} period the real data units / time ratio, whereby the billing follows the actual network load more accurately. Thus, for the user
30 an incentive can be created not to offer the data in bursts but more evenly and thereby contributing to a more efficient network use.

The measuring period can be equal to the interarrival time of two consecutive cells of a same connection. The rate

-6-

over the period from t_i to t_{i+1} and including t_{i+1} is then equal to $1/(t_{i+1} - t_i)$, in other words, the inverse of the difference of the arrival and send times of two consecutive cells. The measuring period can also be longer, e.g. the time between cell number i and cell number $i+n$, where $n > 1$. The measuring period can also be a set period, e.g. 100 ms. It will be appreciated that the shorter the measuring period is, the more accurate the measurements are, but also the larger the calculation capacity of the charging computer has to be. Also, it requires transmission traffic between the charging measurement points and the charging computer.

Registering all measured information for all connections can lead to a large amount of data between the registration device and the billing system. A decrease of the amount of data can be achieved by aggregating the data in an aggregation device and transmitting the aggregated data to the billing system.

~~If a data stream is controlled by the ABR mechanism in ATM,~~
the cell rate assigned (dynamically) by the network is mentioned in the ECR field (Explicit Cell Rate) of so-called backward RM cells. To base the charge, apart from the real transmitted cell rate per measuring period, as proposed in the preceding, also on the capacity assigned by the network, the system can be extended by a device which reads the value that is written in the ECR field. In the same way, the cell rate desired by the user, mentioned in the ECR field of the so-called forward RM cells, can be detected and processed. In that way, the charging is based both on the capacity desire of the user and on the capacity which the network assigns to the user. A comparable function is accomplished in an IP network by reading and registering the size of the reservations desired or made from the reservation messages (e.g. RESV messages of RSVP

[4]), or by reading and registering the priority indication in the header of the IP datagramme, and adjusting the charge accordingly.

DESCRIPTION OF THE FIGURE

5 Figure 1 shows an exemplary embodiment of the invention.
ATM: Asynchronous Transfer Mode

A physical communication line 1 transports ATM cells. The cells can belong to different virtual connections (channels, paths). A measuring device 2 detects from the
10 header of an arriving cell the virtual connection to which the cell belongs. In the measuring device 2 for each (virtual) connection a counter reading is kept up to date with the number of arriving cells. A clock generator 3 generates periodical clock pulses. A calculation device 4
15 calculates per connection the ratio between the number of arrived cells and the number of clock pulses and passes this ratio on to a billing system 5. According to the invention, said ratio is not calculated over the entire
~~time that a connection is active but over smaller periods.~~

20 There are therein two possibilities, viz. (per connection) starting from a fixed measuring period T and counting the number n of cells arriving in that period, wherein the ratio $r = n/T$, or starting from a fixed number of cells N and measuring the time t which is needed for the arriving
25 of those cells, wherein $r = N/t$.

In order to charge a bursty supply of cells more heavily than an even supply, the fixed periods of measurement T or the fixed number of cells N is chosen in such a way that the ratio n/T or N/t is high in traffic with a (temporary)
30 "burst" character. To create an incentive for an even traffic supply, measurement periods in which the value of r is high are charged more heavily than periods with a low value of r .

-8-

In order to let the billing, in a connection which uses ABR, also be dependent on the capacity desired by the user, that value r1 is read by device 2 from passing RM (Resource Management) cells and passed on, through the calculation
5 device 4, to the billing system 5. In the same way a value r2 is extracted, via a return connection 1', in which measuring device 2', a clock generator 3' and a calculation device 4 are included, from the "backward" RM cells, which is an indication for the maximum cell rate which is
10 (dynamically) assigned by the network to the user. That value too, is passed on to the billing system and is included, as well as the value r1, in the price to be charged to the user.

For use in an IP network (where the packet size may vary)
15 the measuring device (2) is moreover able to measure and register the size of the packet (datagramme). The registration includes then the number of IP datagrammes and the cumulative number of bytes in those datagrammes. A
~~calculation device 4 calculates per connection the ration~~
20 between the number of arrived datagrammes/bytes and the number of clock pulses and passes both ratios on to a billing system 5. In the same way, via a return connection 1', in which a measuring device 2', a clock generator 3' and a calculation device 4 are included, a value r2 is in
25 the opposite direction extracted from the reservation messages, which is an indication for the reservation promised by the network. That value too is passed on to the billing system and is included, as well as the value r1, in the price to be charged to the user. Instead of relating to
30 the capacity, the parameters r1 and r2 can also relate to the (requested or assigned) priority of the datagrammes. Optionally, as the figure shows, an aggregation device 6 can be added. This device aggregates the periodically generated data from the calculation devices 4 and 4', so

that the task of the billing system 5 is relieved and the quantity of billing data to be transported is reduced.

REFERENCES

- [1] Marion Raffali-Schreinemachers et al: "Charging and
5 billing issues in high speed heterogeneous networking
environments"; Proceedings InterWorking '96; October 1-3,
1996; Nara, Japan; pp. 97-108.
- [2] ITU-T I.371: "Traffic Control and Congestion Control in
B-ISDN"; ITU-T recommendation I.371 (08/96); Geneva, August
10 1996.
- [3] ITU-T I.356: "B-ISDN ATM layer cell transfer
performance"; ITU-T recommendation I.356 (10/96); Geneva,
October 1996.
- [4] Braden, R. (Ed.), et al: "Resource ReSerVation Protocol
15 (RSVP) Version 1, Functional Specification"; Internet
Engineering Task Force, RFC 2205, September 1997.
-

CLAIMS

1. System for charging the use of a packet based telecommunication network such as an ATM or IP network, characterised by a measuring device (2) for measuring the
5 number (n) of data units received and/or transmitted data units during a set period of time (T), shorter than the time during which said telecommunication connection is opened.
2. System for charging the use of a packet based
10 telecommunication network such as an ATM or IP network, characterised by a measuring device (2) for measuring the time period (t) between a set number (N) of received or transmitted data units.
3. System according to claim 1 or 2, characterised by a
15 calculation device (4) for calculating the number of data units per said period of time (T;t) and supplying that calculation result (r) to a billing system (5).
4. System according to claim 3, in which the
~~telecommunication network comprises system data units~~
20 (RM, RESV) which comprise an indication (r1) of the capacity or priority requested by the user, characterised by a detection device (2) for reading out said indication out of the system data units and transferring that indication to the billing system.
- 25 5. System according to claim 3, in which the telecommunication system comprises system data units (RM, RESV) which comprise an indication (r2) of the capacity or priority assigned by the telecommunication system, characterised by a detection device (2') for reading out
30 said indication out of the system data units and transferring that indication to the billing system.
6. System according to claim 3, characterised by an aggregation device (6) for aggregating the calculation

-11-

result (r) en passant on the aggregated result (ra) to the billing system.

7. System according to claim 4 or 5, characterised by an aggregation device (6) for aggregating said capacity or
5 priority indications (r1, r2) and passing on the aggregated indications (r1a, r2a) to the billing system.
-




FIG. 1

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03950

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04L12/14 H04Q11/04 H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	SAITO H: "RESOURCE MANAGEMENT AND CHARGING IN ATM NETWORKS" COMPUTER NETWORKS AND ISDN SYSTEMS, vol. 28, no. 5, 1 March 1996 (1996-03-01), pages 641-644, XP000555872 paragraph '0002! - paragraph '0004!	1, 3
X	LINDBERGER K: "ANALYTICAL METHODS FOR THE TRAFFICAL PROBLEMS WITH STATISTICAL MULTIPLEXING IN ATM-NETWORKS" TELETRAFFIC AND DATATRAFFIC IN A PERIOD OF CHANGE, COPENHAGEN, JUNE 19 - 26, 1991, no. CONGRESS 13, 19 June 1991 (1991-06-19), pages 807-813, XP000303113	1, 3
Y	JENSEN A; IVERSEN V B paragraph '0006! --- -/-	2

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

14 September 1999

Date of mailing of the international search report

23/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Staessen, B

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03950

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	PATENT ABSTRACTS OF JAPAN vol. 098, no. 008, 30 June 1998 (1998-06-30) & JP 10 079741 A (NIPPON TELEGR & TELEPH CORP & NTT), 24 March 1998 (1998-03-24) abstract	2
A	--- KELLY F P: "TARIFFS AND EFFECTIVE BANDWIDTHS IN MULTISERVICE NETWORKS" FUNDAMENTAL ROLE OF TELETRAFFIC IN THE EVOLUTION OF TELECOMMUNICATIONS NETWORKS, PROCEEDINGS OF THE 14TH. INTERNATIONAL TELETRAFFIC CONGRESS - ITC 1 JUAN-LES-PINS, JUNE 6 - 10, 1994, no. VOL. 1A, 6 June 1994 (1994-06-06), pages 401-410, XP000593430 LABETOULLE J; ROBERTS J W (EDS) abstract	1-7
A	--- VEIRO B: "TRAFFIC MEASUREMENT ON VARIABLE BIT RATE (VBR) SOURCES WITH APPLICATION TO CHARGING PRINCIPLES" COMPUTER NETWORKS AND ISDN SYSTEMS, vol. 20, no. 1 / 05, 1 December 1990 (1990-12-01), pages 435-445, XP000161301 paragraph '0003!	1-7
A	--- EDELL R J ET AL: "BILLING USERS AND PRICING FOR TCP" IEEE JOURNAL ON SELECTED AREAS IN COMMUNICATIONS, vol. 13, no. 7, 1 September 1995 (1995-09-01), pages 1162-1175, XP000525655	1,2
A	--- WO 97 17783 A (NOKIA TELECOMMUNICATIONS OY ;GINZBOORG PHILIP (FI)) 15 May 1997 (1997-05-15) page 4, line 9 - line 22	2
A	--- WO 97 16034 A (ERICSSON TELEFON AB L M) 1 May 1997 (1997-05-01) abstract	1-7

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 99/03950

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 10079741	A	24-03-1998	NONE	
WO 9717783	A	15-05-1997	FI 955406 A	10-05-1997
			AU 7573096 A	29-05-1997
			BR 9611351 A	30-03-1999
			CN 1203716 A	30-12-1998
			EP 0860067 A	26-08-1998
WO 9716034	A	01-05-1997	US 5828737 A	27-10-1998
			AU 7350096 A	15-05-1997

This Page Blank (uspto)
